

# SRM

Radius: **15' to 30'**  
 Flow: **0.42 to 3.4 GPM**  
 Inlet: **½"**

## FEATURES

- Model: 4"
- Arc setting: 40° to 360°
- Nozzle choices: 6
- Nozzle range: 0.50 to 3.0
- Standard factory installed nozzle: 3.0 only
- Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- Water lubricated gear-drive
- Warranty period: 1 year

## OPERATING SPECIFICATIONS

- Radius: 15' to 30'
- Flow: 0.42 to 3.4 GPM
- Recommended pressure range: 30 to 50 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rates: 0.45 in/hr approximately
- Nozzle trajectory: 18° approximately



**SRM-04**  
 Overall height: 6⅝"  
 Pop-up height: 4"  
 Exposed diameter: 1⅝"  
 Inlet size: ½"

ROTORS

SRM	SRM NOZZLES
Model	Description
SRM-04	4" Pop-up, adjustable arc, 6 standard nozzles



SRM



SRM GREEN NOZZLE PERFORMANCE DATA					
Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr	
				■	▲
<b>.50</b> ● Dk. Green	30	15	0.42	0.36	0.41
	<b>40</b>	<b>16</b>	<b>0.50</b>	<b>0.38</b>	<b>0.43</b>
	50	17	0.58	0.39	0.45
<b>.75</b> ● Dk. Green	30	15	0.42	0.36	0.41
	<b>40</b>	<b>16</b>	<b>0.50</b>	<b>0.38</b>	<b>0.43</b>
	50	17	0.58	0.39	0.45
<b>1.0</b> ● Dk. Green	30	19	0.85	0.45	0.52
	<b>40</b>	<b>20</b>	<b>1.0</b>	<b>0.48</b>	<b>0.56</b>
	50	20	1.1	0.53	0.61
<b>1.5</b> ● Dk. Green	30	23	1.3	0.47	0.55
	<b>40</b>	<b>24</b>	<b>1.5</b>	<b>0.50</b>	<b>0.58</b>
	50	25	1.7	0.52	0.60
<b>2.0</b> ● Dk. Green	30	25	1.7	0.52	0.60
	<b>40</b>	<b>26</b>	<b>2.0</b>	<b>0.57</b>	<b>0.66</b>
	50	27	2.3	0.61	0.70
<b>3.0</b> ● Dk. Green	30	28	2.5	0.61	0.71
	<b>40</b>	<b>30</b>	<b>3.0</b>	<b>0.64</b>	<b>0.74</b>
	50	30	3.4	0.73	0.84

**Bold** = Recommended pressure

**Note:**

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.